



ViDeus Mosaic - Technical specifications

Features	VMO-9SDEL-SYS	VMO-16SD-SYS	VMO-32SD-SYS	VMO-16HD-SYS
Maximum reception of SD	9	16	32	64
Maximum HD Pages	1	2	3	3
Maximum SD Pages	2	4	6	6
Network interfaces	1	1	2	2
Supported codecs	MPEG2, MPEG4 (h.264), AAC, AAC LATM, MPEG2 Layer3, MPEG1 Layer2, AC3.			
Reception transport	SPTS y MPTS, unicast or multicast.			
Licenses	Unlimited for administration and visualization.			
Power supply	Simple	Simple	1 + 1 redundant	1 + 1 redundant
Chassis	VESA	3RU	2RU	2RU
Additional supported hardware	-	HDMI/SDI (VMO-SDI-OP) Output.		



2RU Chassis

Height:	90mm
Width:	430mm
Length:	660mm
Input voltage:	110v / 230v
Power:	650 VA

3RU Chassis

Height:	135mm
Width:	425mm
Length:	500mm
Input voltage:	110v / 230v
Power:	500 VA

Pro Chassis

Redundant forced ventilation
Backplane
Rack guides
Hot-swap hard disk

Mini form factor (VESA) chassis specifications

Height:	55mm
Width:	110mm
Length:	111mm
Power supply:	input voltage: AC 100-240V, output: DC 19V 3.42 A
USB ports:	2

